

SDS 18-10-2019 SX V03 UK

Product name: Nexa3D xCE-White

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name Nexa3D xCE-White

Produce description Photopolymer Resin for 3D-printing (SLA, DLP & LCD)

Alternative names Ligcreate extra strong resin, Ligcreate SX, Ligcreate engineering resin

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use Photopolymer is monomer based on acrylic esters for SLA and/or DLP 3D

printers with UV-light systems.

Uses advised against

1.3 Details of the supplier of the safety data sheet

Nexa3D, Inc.

1923 Eastman Ave. STE200

Ventura, CA 93003

USA

Tel.: 1-805-465-9001 info@nexa3d.com

1.4 Emergency Telephone Number

ChemTel 1-800-255-3924 (US) / 1-813-248-0585 Contract

MIS3892732

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to Regulation (EG) No. 1272/2008 [CLP]

2 Skin sens. Cat. 1 H317 Eye irrit. Cat. 1 H319 Aquatic chronic Cat. 4 H413

2.2 Label elements



Signal word Warning

Hazerd statement(s) H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H413: May cause long-lasting harmful effects to aquatic life.

Precautionary statement(s) P280: Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264: Wash thoroughly after handing.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P302+P352: IF ON SKIN: Wash with plenty of water.



P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/container in accordance with local/regional/national/

international regulation.

2.3 Other Hazards

Not classified as PBT or vPvB.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture.

3.2 Mixtures

Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.

According to Regulation (EG) Nr. 1272/2008 [CLP]

Hazardous ingredient(s)	%W/W	EINECS No.	Hazard Class and Category Code(s)	Harzard statement Code(s)
Methacrylic Oligomer	65 - 85	Proprietary	Skin sens. Cat. 1 Aquatic chronic Cat. 4	H317 H413
Glycol Methacrylate	10 - 30	212-782-2	Skin sens. Cat. 1 Eye irrit. Cat. 2	H317 H319
Benzoxazole	<0,5	230-426-4	Aquatic Chronic Cat. 4	H413
Phosphine Oxide	≤3,0	278-355-8	Skin sens. Cat. 1 Repr. Cat. 2 (fer.) Aquatic chronic Cat. 2	H317 H361f H411

For full text of H phrases see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation IF INHALED: Move into fresh air and keep at rest. Get medical attention if any discomfort

continues.

Skin Contact IF ON SKIN (or hair): Remove contaminated clothing immediately and wash skin with

soap and water. Get medical attention promptly if irritation or other symptoms occur after

washing.

Eye Contact

IF IN EYES: Continue to rinse for at least 15 minutes under running water with eyelids held

open. Get medical attention.

Ingestion

Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediately rinse mouth and drink plenty of water. Keep

person under observation. If person becomes uncomfortable get medical attention.

SATETY DATA SHEET

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further important symptoms and effects are so fat not known.

4.1 Description of first aid measures

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguising media

Suitable Extinguishing Media Water spray, dry powder, CO2/

Unsuitable Extinguishing Media Water jet.t

5.2 Special hazards arising from the substance or mixture

Hazards during fire-fighting Harmful vapours

Evolution of fumes/fog

High temperatures may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. Use a water spray or fog to reduce temperature of containers.

5.3 Advice for fire-fighters

Protective equipment Wear a self-contained breathing apparatus and full protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use protective gloves, goggles and suitable protective clothing. In case of inadequate ventilation, use respiratory protection. Maximize ventilation after accidental release.

6.2 Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater. Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Remove sources of ignition. Absorb with sand or other inert absorbent. Spillage may be stored as chemical waste in approved area.

6.4 Reference to other sections

See section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Use mechanical ventilation in case of handling which cases formation of vapours. Handle and open container with care. Wear full protective clothing for prolonged exposure and/or high concentrations. Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Protect from light, including direct sunrays. Container may be filled for only 90%. Keep containers tightly closed, separate from oxidizing agents. Store in original container in a dry, cool and well-ventilated place. Store at temperatures between 5°C and 30°C. Do not expose to temperatures above 50°C for more than 24 hours. High temperatures may cause spontaneous polymerization.



7. 3 Specific end use(s)

None.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Substance	EC No.
Methacrylic Oligomer (100%)	Proprietary

DNEL (100% component)	Oral	Inhalation	Dermal
Worker - Long Term - Systemic effects	1	1	1

PNEC (100% component)	
Aquatic Compartment	Not applicable
Terrestrial Compartment	Not applicable

1 Toxicity: DNEL not established

Substance	EC No.	LTEL ppm (8 Hr TWA)	LTEL mg/m³ (8 h TWA)
Glycol Methacrylate (100%)	212-782-2	0,05	0,24

DNEL (100% component)	Oral	Inhalation	Dermal
Worker - Long Term - Systemic effects	1	4,9 mg/m ³	1,3 mg/kg

PNEC (100% component)	
Aquatic Compartment	10 mg/l (Fresh water) 0,482 mg/l (Sea water) 3,79 mg/kg dry weight (sediment)
Terrestrial Compartment	0,476 mg/kg dry weight

1 Toxicity: DNEL not established

Substance	EC No.
Phosphine Oxide (100%)	278-355-8

DNEL (100% component)	Oral	Inhalation	Dermal
Worker - Long Term - Systemic effects	1	3,5 mg/m ³	1,0 mg/kg



PNEC (100% component)	
Aquatic Compartment	0,00353 mg/l (Fresh water) 0,000353 mg/l (Sea water) 0,29 mg/kg dry weight (sediment)
Terrestrial Compartment	0,0557mg/kg dry weight

1 Toxicity: DNEL not established

Substance	EC No.
Phosphine Oxide (100%)	230-426-4

DNEL (100% component)	Oral	Inhalation	Dermal
Worker - Long Term - Systemic effects	1	1	1

PNEC (100% component)	
Aquatic Compartment	Not applicable
Terrestrial Compartment	Not applicable

1 Toxicity: DNEL not established

8.2 Exposure controls

Appropriate engineering controls

Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection Wear eye/face protection. Wear approved chemical safety goggles where eyes

Skin protection Wear suitable gloves. Butyl and nitrile rubber gloves offer short-term protection.

Later surgical gloves offer little protection. Gloves should be stored correctly and

changed regularly, especially if excessive exposure has occured.

Respiratory protection Wear suitable respiratory protective equipment if engineering controls are

insufficient, or not present, and exposure to leves above the DNEL is likely. A

suitable mask with filter type A (EN141 or EN405) may be appropriate.

Other Keep working clothes separately. Take off contaminated clothing immediately. Wash

soiled clothing before reuse. Keep away from food, drinks and animal feed. Wash

hands thoroughly after handling.

Environmental exposure controls

Ensure effective control measures when working within the boundaries as specified in section 6.2 of each GES.



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Viscous liquid - grey or orange (but different colors possible)

Odour Ester like
pH Not applicable
Melting point Not applicable
Boiling point > 200°C
Flash point > 150°C

Flammable Limites (lower) (%v/v) Not applicable

Vapour pressure Solubility (Water) Not soluble

Solubility Good solubility with most organic solvents

Auto ignition temperature 380°C

Explosive properties

Oxidising properties

Relative density

Viscosity

Not applicable

1.1-1.2 (water = 1)

0.5-1.1 Pa•s

9.2 Other information

None.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

See part 10.2

10.2 Chemical stability

Stable under normal temperature conditions. Stable is stored and handled as prescribed/indicated.

10. Possibility of hazardous reactions

Hazardous polymerization. May polymerize.

10.4 Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with free radical initiators. Avoid contact with isocyanates and oxidizing agents. Avoid contact with vinyl polymerization initiators. Avoid exposure to high temperatures, direct sunlight or ultra voilet (UV) radiation.

10.5 Incompatible materials

Avoid contact with radical forming initiators, peroxides, strong alkalies or reactive metals to prevent exothermic polymerization.

10.6 Hazardous Decomposition Product(s)

With regard to possible decomposition products refer to Section 5: Oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Stable Acute toxicity:

Methacrylic Oligomer (100%)

LD50 acute

Skin irritation

Eye irritation

No information available

No aspiration hazard expected



Glycol Methacrylate (100%)

LD50 acute oral rat > 5000 mg/kg LD50 acute dermal rabbit > 5000 mg/kg Skin irritation (rabbit, 24 h, Draize) non-irritant Eye irritation (rabbit, Draize) Irritating Inhalation (guinea pig, GPMT) Sensitizing

Aspiration Hazard no aspiration hazard expected

Chronic toxicity oral rat (OESO 422) > 100 mg/kg

Reproductive toxicity (animal studies)

No suspicion of a toxic effect on reproduction

Phosphine Oxide (100%)

LD50 acute dermal rat: >2000 mg/kg Skin irritation (rabbit, 24 h, Draize) Non-irritant Eye irritation (rabbit, Draize) Non-irritant Skin sensitation mouse LLNA (OESO 429) Sensitizing

Aspiration Hazard No aspiration hazard expected

Chronic toxicity (animal studies) May cause damange after repeated ingestion of high doses

Reproductive toxicity (animal studies)

Suggest a fertility impairing effect

Benzoxale (100%)

Skin irration Non-irritant
Skin sensation No sensitization

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Methacrylic Oligomer (100%) Toxicity to fish (mg/l) Aquatic invertebrates (mg/l) Aquatic plants (mg/l) Microorganisms (mg/l)	LL50 (96 h) (Oncorhynchus mykiss) (OESO 203) EL50 (72 h) (Daphnia magna) (OESO 202) EL50 (72 h) (Pseudokirchneriella subcapitata) (OECD 201) NOEC (72 h) (Selenastrum capricornutum) (OESO 201) NOEC (28 d) (Activated suldge) (DEV L8)	No data available No data available No data available No data available No data available
Glycol Methacrylate (100%)		
Toxicity to fish (mg/l)	LC50 (96 h) (Oryzias latipes) (OESO 203)	>100
Aquatic invertebrates (mg/l)	NOEC (21 d) (Daphnia magna) (OESO 202)	24,1
	EC50 (48 h) (Daphnia magna) (OESO 202)	380
Aquatic plants (mg/l)	EC50 (72 h) (Selenastrum capricornutum) (OESO 201)	836
	NOCE (72 h) (Selenastrum capricornutum) (OESO 201)	400
Microorganisms (mg/l)	EC50 (16 h) (Pseudomonas fluorescens) (DEV L8)	>3000
Phosphine Oxide (100%)		
Toxicity to fish (mg/l)	LC50 (96 h) (Brachydanio rerio) (OESO 203)	>90
Aquatic invertebrates (mg/l)	EC50 (48 h) (Daphnia magna) (OECD 202)	>1175
Aquatic plants (mg/l)	EC50 (72 h) (Desmodesmus subspicatus) (OECD 201)	>260
Microorganisms (mg/l)	EC50 (3 h) (Activated sludge) (DEC L8)	>100
Benzoxazole (100%)		
Toxicity to fish (mg/l)	LC50 (96 h) (Brachydanio rerio) (OESO 203)	>100



12.2 Persistence and degradability

Methacrylic Oligomer (100%)

No data available.

Glycol Methacrylate (100%)

Easy biodegradable.

Elimination information:

84% DOC reduction (28 d) (OESO 301 D)

Phosphine Oxide (100%)

Poorly biodegradable. No readily biodegradable (by OECD criteria)

Elimination information:

< 20% BOD of the ThOD (28 d) (OECD 301 F) (activated sludge)

Benzoxazole (100%)

No data available.

12.3 Bioaccumulative potential

Methacrylic Oligomer (100%)

No data available.

Glycol Methacrylate (100%)

Accumulation in organisms is not to be expected.

Phosphine Oxide (100%)

Does not significantly accumulate in organisms.

Bioconcentration factor: 23 - 55 (56 d), Cyprinus carpio (measured): does not significantly accumulate in organisms.

Benzoxazole (100%)

No data available.

12.4 Mobility in soil

Methacrylic Oligomer (100%)

No data available.

Glycol Methacrylate (100%)

The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is not expected.

Phosphine Oxide (100%)

The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is not expected.

Benzoxazole (100%)

No data available.

12.5 Results of PBT and vPvB assessment

Methacrylic Oligomer (100%)

PBT: no

Glycol Methacrylate (100%)

PBT: no vPvB: no



Phosphine Oxide (100%)

PBT: no vPvB: no

Benzoxazole (100%)

PBT: no vPvB: no

12.6 Other adverse effects

Methacrylic Oligomer (100%)

No data available.

Glycol Methacrylate (100%)

Do not allow to enter soil, waterways or waste water channels.

Phosphine Oxide (100%)

Not applicable.

Benzoxazole (100%)

Not applicable.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations. Incinerate under approved controlled conditions, using incinerators for the disposal for organic chemicals. Decontaminate empty drums before recycling.

SECTION 14: TRANSPORTATION INFORMATION

14.1 UN-Nummer

Not classified as a dangerous good under transport regulations.

14.2 UN Proper Shipping Name

Not applicable.

14.3 Transport hazard class(es)

Not applicable.

14.4 Packing group

Not applicable.

14.5 Environmental hazards

Toxic to aquatic life with long lasting effects.

14.6 Special precautions for user

_

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

-

NeX33D°

SATETY DATA SHEET

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

If information other than the information in relation to safety, health and environmental regulations/legislation what is mentioned elsewhere in this Safety Data Sheet is requied, please use the information listed in Section 1 to inquire whether that specific information is available. Related information about the separate components in the mixture can be accessed the same way.

15.2 Chemical Safety Assessment

A Chemical Safety Assessement has been carried out for the following individual component (100%): Glycol Methacrylate.

SECTION 16: OTHER INFORMATION

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 453/2010.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such materials used in combination with any other materials or in any process unless specified in the text.

LEGEND

Note: Not all of the following are necessarily contained in this Safety Data Sheet:

WEL: Workplace Exposure Limit.

Sen: Capable of causing respiratory sensitization.

Sk: Can be absorbed through skin.

Carc: Capable of causing cancer and/or heritable genetic damage.

LTEL: Long Term Exposure Limit.

STEL: Short Term Exposure Limit.

TWA: Time Weighted Average.

STOT SE: Specific Target Organ Toxicity – Single Exposure.

Repr.: Reproductive toxicity.

Aquatisch acute/chronic: Hazardous to the aquatic environment.

Full text of H/P/R phrases

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H361f: Suspected of damaging fertility.

H411: Toxic to aquatic life with long-lasting effects.

H413: May cause long-lasting harmful effects to aquatic life.

P261: Avoid breathing vapours.

P264: Wash (hands and exposed skin) thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinerate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics.